


**NEW!**

# High Power PoE Signal Path Magnetics



- Meets the current requirements of Gigabit PoE Plus.
- Open circuit inductance is  $\geq 350 \mu\text{H}$  with a 22.5 mA dc offset
- Handle up to 800 mA.

**Core material** Ferrite

**Terminations** RoHS Tin-silver-copper over tin over nickel over phos bronze. Other terminations available at additional cost.

**Weight** HPF2187L: 200 mg; HPX2126L: 3.8 g

**Ambient temperature**  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$

**Storage temperature** Component:  $-55^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ .  
Packaging:  $-55^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$

**Resistance to soldering heat** Max three 40 second reflows at  $+260^{\circ}\text{C}$ , parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at  $<30^{\circ}\text{C}$  / 85% relative humidity)

**Mean Time Between Failures (MTBF)** 26,315,789 hours

#### Packaging

**HPF2187L:** 500/7" reel; 2000/13" reel; Plastic tape: 16 mm wide, 0.35 mm thick, 8 mm pocket spacing, 4.4 mm pocket depth

**HPX2126L:** 300/13" reel; Plastic tape: 32 mm wide, 0.5 mm thick, 20 mm pocket spacing, 11 mm pocket depth

**PCB washing** Only pure water or alcohol recommended

## Isolation Transformer

Part number <sup>1</sup>	Inductance <sup>2</sup> ( $\mu\text{H}$ )	DCR max <sup>3</sup> (Ohms)	Isolation <sup>4</sup> (Vrms)
HPX2126L_	850	0.24	1500

1. When ordering, please specify **packaging** code:

**HPX2126LD**

**Packaging:** **D** = 13" machine-ready reel. EIA-481 embossed plastic tape (300 parts per full reel).

**B** = Less than full reel. In tape, but not machine ready.  
To have a leader and trailer added (\$25 charge), use code letter D instead.

- Inductance measured at 100 kHz, 0.1 Vrms, 0 Adc.
- DCR is for each winding.
- Isolation is measured from primary to secondary of each transformer.
- Operating temperature range  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ .
- Electrical specifications at  $25^{\circ}\text{C}$ .

## Common Mode Choke

Part number <sup>1</sup>	Inductance <sup>2</sup> ( $\mu\text{H}$ )	DCR max <sup>3</sup> (Ohms)
HPF2187L_	10.0	0.15

1. When ordering, please specify **packaging** code:

**HPF2187LC**

**Packaging:** **C** = 7" machine-ready reel. EIA-481 embossed plastic tape (500 parts per full reel).

**B** = Less than full reel. In tape, but not machine ready.  
To have a leader and trailer added (\$25 charge), use code letter C instead.

**D** = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (2000 parts per full reel).

- Inductance measured at 100 kHz, 0.1 Vrms, 0 Adc.
- DCR is for each winding.
- Operating temperature range  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ .
- Electrical specifications at  $25^{\circ}\text{C}$ .

# Coilcraft®

Specifications subject to change without notice.  
Please check our website for latest information.

Document 489-1 Revised 04/15/08


1102 Silver Lake Road Cary, Illinois 60013 Phone 847/639-6400 Fax 847/639-1469

E-mail [info@coilcraft.com](mailto:info@coilcraft.com) Web <http://www.coilcraft.com>




**NEW!**

# High Power PoE Signal Path Magnetics




Note 1. C1 = 8 pF minus the output capacitance of the chipset

## Isolation Transformer HPX2126L



## Common Mode Choke HPF2187L



Specifications subject to change without notice.  
Please check our website for latest information.

Document 489-2 Revised 04/15/08

1102 Silver Lake Road Cary, Illinois 60013 Phone 847/639-6400 Fax 847/639-1469

E-mail info@coilcraft.com Web http://www.coilcraft.com

**NEW!**

# High Power PoE Signal Path Magnetics

## Description

Coilcraft's signal path magnetics meet the current requirements of Gigabit Ethernet PoE Plus. The open circuit inductance is  $\geq 350 \mu\text{H}$  with a 22.5 mA dc offset applied from 0°C to 70°C. It can handle 800 mA of current.

The system comprises an isolation transformer, a common mode choke and six capacitors. The capacitor across the primary of the isolation transformer on the TX side tunes the circuit by matching the output capacitance of the chipset allowing these components to be used with virtually all chipsets.

The two isolation transformers are placed in a single package (HPX2126L) and both common mode chokes in an even smaller package (HPF2187L). Both packages fit easily behind a standard Ethernet jack.

## Testing

A matching network is used to perform the testing for return loss, insertion loss, crosstalk, common mode to common mode rejection and differential to common mode rejection. The network matches the 50 Ohm single ended connection of network analyzers to 100 Ohm differential balanced lines. A 1:1 balun is used with a resistive network to transform the impedance. The net-

work is then calibrated out of the measurement by using open, short, load calibration techniques. The circuit is then placed behind the matching network for each of the tests. All tests are performed on an Agilent/HP 8753ES network analyzer.

For return loss, the chip side of the component is loaded with 100 Ohms and the cable side of the system is tested using the matching network.


For insertion loss, the fixture used for the return loss is altered to replace the 100 Ohm load with a matching network for the output port of the network analyzer.

For common mode to common mode rejection, TX+ and TX- (or RX+ & RX-, depending on the side of the system) is tied together and an S21 measurement is taken from chip side to cable side.

For differential to common mode rejection, the chip side of the system is excited by the network analyzer through the matching network. The measurement is taken by looking at the balance between two 50 Ohm loads across the cable side of the system.


For crosstalk, the chip side TX is excited by the network analyzer through the matching network. The center-tap on the chip side of each isolation transformer is grounded, and the chip side RX is measured. The cable side of both RX and TX is externally loaded 100 Ohms.

## Return Loss



802.3af specification:  
 18 dB min from 1 MHz to 40 MHz  
 16 dB min at 50 MHz  
 12 dB min at 80 MHz  
 10 dB min at 100 MHz

## Insertion Loss



802.3af specification:  
 1.0 min dB from 0.1 MHz to 100 MHz  
 1.2 min dB at 125 MHz

# Coilcraft®

Specifications subject to change without notice.  
 Please check our website for latest information.

Document 489-3 Revised 04/15/08

1102 Silver Lake Road Cary, Illinois 60013 Phone 847/639-6400 Fax 847/639-1469


E-mail [info@coilcraft.com](mailto:info@coilcraft.com) Web <http://www.coilcraft.com>



**NEW!**


# High Power PoE Signal Path Magnetics

## Common Mode Rejection




802.3af specification:  
 50 dB min from 1 MHz to 10 MHz  
 30 dB min from 10 MHz to 125 MHz  
 20 dB min from 125 MHz to 500 MHz

## Differential to Common Mode Rejection




802.3af specification:  
 45 dB min at 30 MHz  
 40 dB min at 60 MHz  
 35 dB min at 100 MHz

## Crosstalk



802.3af specification:  
 45 dB min at 30 MHz  
 40 dB min at 60 MHz  
 33 dB min at 100 MHz

## L vs Offset Current – HPX2126L



Specifications subject to change without notice.  
 Please check our website for latest information.

Document 489-4 Revised 04/15/08

1102 Silver Lake Road Cary, Illinois 60013 Phone 847/639-6400 Fax 847/639-1469

E-mail [info@coilcraft.com](mailto:info@coilcraft.com) Web <http://www.coilcraft.com>