



NEW!

Surface Mount Tip and Ring Filters



These surface mount tip and ring filters provide substantial reduction of noise throughout an extended frequency range. Their economical design makes them attractive for a wide variety of applications.

Free evaluation samples are available by contacting Coilcraft or ordering them on-line at www.coilcraft.com.

Part number ¹	PTRF2000L_	PTRF4000L_
Lines	1	2
Minimum inductance: (each winding @ 130 kHz)	35 μ H	35 μ H
Rated current:	500 mA	500 mA
DCR each winding:	0.075 Ω max	0.135 Ω max
Dielectric strength:	1500 Vrms (1-8)	1500 Vrms (1,2-7,8)

1. When ordering, please specify **packaging** code:


PTRF4000L C

Packaging: C = 7" machine ready reel. EIA-481 embossed plastic tape, 500 parts per full reel.

B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.


D = 13" machine ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked, 2200 parts per full reel.

2. Operating temperature range -40°C to +85°C.
3. Electrical specifications at 25°C.



Weight: 214 – 216 mg
Termination: Tin-silver-copper over tin over nickel over phos bronze
Tape and reel: 500/7" reel; 2000/13" reel 16 mm tape width
For packaging data see Tape and Reel Specifications section.

Typical Response**



Coilcraft[®]

Specifications subject to change without notice.
Please check our website for latest information.

Document 492 Revised 11/10/05

1102 Silver Lake Road Cary, Illinois 60013 Phone 847/639-6400 Fax 847/639-1469
E-mail info@coilcraft.com Web <http://www.coilcraft.com>